

Nozzle Schedule

Mark	Size	Position	Service
N1	1"	330°	Product Inlet
N2	3"	180°	Sight Glass
N3	2"	220°	Light Glass
N4	1"	0°/360°	Vacuum
N5	2"	45°	Spare
N6	R ^{3/8"}	60°	Heating Base In
N7	R ^{3/8"}	60°	Heating Base Out
N8	R ^{3/8"}	60°	Heating Vessel In
N9	R ^{3/8"}	60°	Heating Vessel In
N10	1 ^{1/2"}	90°	Filtrate Outlet
*N11	1"	180°	Sample
*N12	3"	270°	Side Discharge
N13	1/2"	300°	Nitrogen
N14	1"	250°	Manometer
*N15	3"	270°	Cake Discharge
N18	ø8	270°	Compressed Air
N19 ₁	G ^{1/8"}	90°	Leakage (Mech. Seal)
*N19 ₂	G ^{1/4"}	90°	Nitrogen (Mech. Seal)
T1	-	90°	Temperature Sensor

(*Optional)

Technical Data

Min/Max allowable pressure (PS)	-1+6 bar
Min/Max allowable temp. (TS)	-10/+150° C
Total Volume (vessel)	122 L
Material	316L / HC-22
Weight Empty	510 kg
Drive	FL Vario
Torque	370 Nm
Agitator Speed	8.1-40 RPM
Main Motor	2HP / 1800 RPM

